

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

RAMSET EPOXY PASTE 1210 PART B

SYNONYMS

"Product Code: EP1210BL2, EP1210BL10"

PRODUCT USE

■ Used according to manufacturer's directions.

Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

SUPPLIER

Company: ITW Australia Pty Ltd (Ramset)

Address:

1 Ramset Drive

Chirnside Park

VIC, 3116

Australia

Telephone: 1300 780 063

Telephone: +61 3 9726 6222

Emergency Tel: **1800 039 008 (24 hrs)**


Email: www.ramset.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

Risk Codes

R20/22

R36/38

R43

Risk Phrases

• Harmful by inhalation and if swallowed.

• Irritating to eyes and skin.

• May cause SENSITISATION by skin contact.

SAFETY

Safety Codes

S24

S25

S36

S37

S39

S51

S09

S401

Safety Phrases

• Avoid contact with skin.

• Avoid contact with eyes.

• Wear suitable protective clothing.

• Wear suitable gloves.

• Wear eye/face protection.

• Use only in well ventilated areas.

• Keep container in a well ventilated place.

• To clean the floor and all objects contaminated by this material, use water and detergent.

S13

• Keep away from food, drink and animal feeding stuffs.

S26

• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

S46

• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 2 of 7

Section 2 - HAZARDS IDENTIFICATION

this container or label).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
fatty acids C18/ tall oil/ tetraethylenepentamine oligomer	103758-98-1	30-60
ingredients at levels determined not to be hazardous [Mfr]		balance

Section 4 - FIRST AID MEASURES

SWALLOWED

- - IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
- For advice, contact a Poisons Information Centre or a doctor.
- Urgent hospital treatment is likely to be needed.
- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- for poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
 - Watch for signs of respiratory insufficiency and assist ventilation as necessary.
 - Administer oxygen by non-rebreather mask at 10 to 15 L/min.
 - Monitor and treat, where necessary, for pulmonary oedema .
- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- - Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 3 of 7

Section 5 - FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

■ - Combustible.

- Slight fire hazard when exposed to heat or flame.

- Heating may cause expansion or decomposition leading to violent rupture of containers.

- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

■ - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

■ - Clean up all spills immediately.

- Avoid contact with skin and eyes.

- Wear impervious gloves and safety goggles.

- Trowel up/scrape up.

MAJOR SPILLS

■ - Clear area of personnel and move upwind.

- Alert Fire Brigade and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves.

- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

■ - Avoid all personal contact, including inhalation.

- Wear protective clothing when risk of exposure occurs.

- Use in a well-ventilated area.

- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

■ - Metal can or drum

- Packaging as recommended by manufacturer.

- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

■ - Avoid reaction with oxidising agents.

- Avoid strong acids, bases.

Avoid reaction with

amines.

STORAGE REQUIREMENTS

■ - Store in original containers.

- Keep containers securely sealed.

- Store in a cool, dry, well-ventilated area.

- Store away from incompatible materials and foodstuff containers.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

• fatty acids C18/ tall oil/ tetraethylenepentamine oligomer:

CAS:103758- 98- 1

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012
9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 4 of 7

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA

FATTY ACIDS C18/ TALL OIL/ TETRAETHYLENEPENTAMINE OLIGOMER:

RAMSET EPOXY PASTE 1210 PART B:

- Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

RAMSET EPOXY PASTE 1210 PART B:

■ Amine adducts have much reduced volatility and are less irritating to the skin and eyes than amine hardeners. However commercial amine adducts may contain a percentage of unreacted amine and all unnecessary contact should be avoided.

Amine adducts are prepared by reacting excess primary amines with epoxy resin.

PERSONAL PROTECTION

RESPIRATOR

•Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

■ - Safety glasses with side shields.

- Chemical goggles.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

■ - Wear chemical protective gloves, e.g. PVC.

- Wear safety footwear or safety gumboots, e.g. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

OTHER

■ - Overalls.

- P.V.C. apron.

- Barrier cream.

- Skin cleansing cream.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Grey paste.

PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

State	Non Slump Paste	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	154 (PMCC)	pH (1% solution)	Not Available
Decomposition Temp (°C)	>350	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 5 of 7

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.25
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	<1	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Product is considered stable and hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
- Ingestion of amine epoxy-curing agents (hardeners) may cause severe abdominal pain, nausea, vomiting or diarrhoea. The vomitus may contain blood and mucous. If death does not occur within 24 hours there may be an improvement in the patients condition for 2-4 days only to be followed by the sudden onset of abdominal pain, boardlike abdominal rigidity or hypo-tension; this indicates that delayed gastric or oesophageal corrosive damage has occurred.

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin oncontact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling. Blistering, with weeping of serous fluid, and crusting and scaling may also occur. Individuals exhibiting "amine dermatitis" may experience a dramatic reaction upon re-exposure to minute quantities. Highly sensitive persons may even react to cured resins containing trace amounts of unreacted amine hardener. Minute quantities of air-borne amine may precipitate intense dermatological symptoms in sensitive individuals. Prolonged or repeated exposure may produce tissue necrosis.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing "amine asthma". The literature records several instances of systemic intoxications following the use of amines in epoxy resin systems.

CHRONIC HEALTH EFFECTS

- Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.
- There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.
- Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing "amine asthma". The literature records several instances of systemic intoxications following the use of amines in epoxy resin systems.
- Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling. Blistering, with weeping of serous fluid, and crusting and scaling may also occur. Individuals exhibiting "amine dermatitis" may experience a dramatic reaction upon re-exposure to minute quantities. Highly sensitive persons may even react to cured resins containing trace amounts of unreacted amine hardener. Minute quantities of air-borne amine may precipitate intense dermatological symptoms in sensitive individuals. Prolonged or repeated exposure may produce tissue necrosis.

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 6 of 7

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
fatty acids C18/ tall oil/ tetraethylenepentamine oligomer	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

- - Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.
- Otherwise:
 - If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
 - DO NOT allow wash water from cleaning or process equipment to enter drains.
 - It may be necessary to collect all wash water for treatment before disposal.
 - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 - Where in doubt contact the responsible authority.
 - Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Authority for disposal.
 - Bury or incinerate residue at an approved site.
 - Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xn Harmful

POISONS SCHEDULE S5

REGULATIONS

Regulations for ingredients

No data for Ramset Epoxy Paste 1210 Part B (CW: 4773-99)

continued...

RAMSET EPOXY PASTE 1210 PART B

Chemwatch Independent Material Safety Data Sheet

Issue Date: 25-Jan-2012

9317SP(cs)

CHEMWATCH 4773-99

Version No:2.1.1.1

CD 2012/4 Page 7 of 7

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 25-Jan-2012

Print Date: 25-Jan-2013

This is the end of the MSDS.