Material Safety Data Sheet



1. Identification of the material and supplier

<u>Names</u>	
Product name	: Sikadur 52 Part A
ADG	: Environmentally hazardous substance, liquid, n.o.s.
<u>Supplier</u>	
Supplier/Manufacturer	: Sika Australia Pty. Ltd. 55 Elizabeth Street (Locked Bag 482 BDC) Wetherill Park, NSW 2164 Australia
Telephone no.	: +61 2 9725 11 45
Fax no.	: +61 2 9725 33 30
Emergency telephone number	: +61 1800 033 111
Use of the substance/mixture	: Chemical product for construction and industry

2. Hazards identification

Classification	: Xi; R36/38 R43 N; R51/53
Risk phrases	 R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	: S24- Avoid contact with skin. S37- Wear suitable gloves. S61- Avoid release to the environment. Refer to special instructions/safety data sheet.
Statement of hazardous/dangerous nature	: HAZARDOUS SUBSTANCE. DANGEROUS GOODS.

3. Composition/information on ingredients

Mixture	: Yes.		
	ict. bisphenol-A-(epichlorhydrin) and epoxy resin age molecular weight <= 700)	25068-38-6	60 - 100
oxirane, mono	[(C12-14-alkyloxy)methyl]derivs	68609-97-2	1 - <10
Hydrocarbons	, C10-C13, aromatic, >1% Naphthalene	64742-94-5	1 - <10
naphthalene		91-20-3	0.1 - <1

Other ingredients, determined not to be hazardous according to Safe Work Australia criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First-aid measures

First-aid measures

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Sikadur 52 Part A

4. First-aid measures	
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measu	res
------------------------	-----

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	In a fire or if heated, a pressure increase will occur and the container may burst.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazchem code	: 3Z

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6. Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limit	<u>S</u>
Ingredient name naphthalene	Exposure limits Safe Work Australia (Australia, 8/2005). STEL: 79 mg/m ³ 15 minute(s). STEL: 15 ppm 15 minute(s). TWA: 52 mg/m ³ 8 hour(s). TWA: 10 ppm 8 hour(s).
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Exposure controls	
Engineering measures	: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eyes	 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Hands	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Version :	1 Page: 3/6

8. Exposure controls/personal protection

	• •
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid. [Liquid.]
Colour	: Yellow.
Odour	: Characteristic.
Vapour pressure	: 0.02 kPa (0.15 mm Hg) [20°C]
Density	: 1.15 g/cm ³ [20°C (68°F)]
Flash point	: Closed cup: 112°C (233.6°F)
рН	: 7.7
Solubility	: Insoluble in the following materials: cold water.

10. Stability and reactivity

Stability	: The product is stable.
Conditions to avoid	: No specific data.
Materials to avoid	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Potential acute health effects

Version :

Potential acute nealth enects						
Inhalation	:	No known significant effects or critical hazards.				
Ingestion	:	Irritating to mouth, throat and stomach.				
Skin contact	:	Irritating to skin. May cause sensitisation by skin contact.				
Eye contact	:	Irritating to	o eyes.			
Acute toxicity						
Product/ingredient name reaction product: bisphenol-A (epichlorhydrin); epoxy resin	۱-		Result LD50 Dermal	Species Rabbit	<mark>Dose</mark> ≥20000 mg/kg	Exposure -
			LD50 Oral	Rat	>5000 mg/kg	-
naphthalene			LD50 Oral	Rat	500 mg/kg	-
Conclusion/Summary		Not availa	ble.			
Potential chronic health effec	<u>ts</u>					
Chronic toxicity						
Conclusion/Summary	÷	Not availa	ble.			
Carcinogenicity						
Conclusion/Summary	:	Not availa	ble.			
Mutagenicity						
Conclusion/Summary	1	Not availa	ble.			
Teratogenicity						
Conclusion/Summary	:	Not availa	ble.			
Reproductive toxicity						
Conclusion/Summary	:	Not availa	ble.			
Chronic effects	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.				
Carcinogenicity	:	No known	significant effects	s or critical hazards	S	

1	Page: 4/6
---	-----------

11. Toxicological information Mutagenicity : No known significant effects or critical hazards.

Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness
Eyes	: Adverse symptoms may include the following: irritation watering redness

12. Ecological information

Environmental effects	:	Toxic to aquatic organism environment.	s, may cause long-term adv	verse effects in the aquatic
Aquatic ecotoxicity				
Conclusion/Summary	:	Not available.		
Other ecological information				
Biodegradability				
Conclusion/Summary	:	Not available.		
Bioaccumulative potential				
Product/ingredient name		LogP _{ow}	BCF	Potential
naphthalene		3.3	85.11380382	low
Other adverse effects	:	No known significant effect	cts or critical hazards.	

13. Disposal considerations

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

ADG	
UN number	: UN3082
ADG Class	: 9
Packing group	: III
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
Contains	: Epoxide resin
Label No.	: 9
Hazchem code	: 3Z
ADR	
UN number	: UN3082
ADR Class	: 9
Classification code	: M6
Packing group	: 111
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.

1

Sikadur 52 Part A			
14. Transport information			
Contains	: Epoxide resin		
Label No.	: 9		
<u>IMDG</u>			
UN number	: UN3082		
IMDG Class	: 9		
Packing group	: III		
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.		
Contains	: Epoxide resin		
Emergency schedules (EmS)	: F-A, S-F		
Marine pollutant	: Yes.		
Label no.	: 9		
IATA			
UN number	: UN3082		
IATA Class	: 9		
Packing group	: 111		
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.		
Contains	: Epoxide resin		
Label no.	: 9		

15. Regulatory information

Standard for the Uniform Sc	heduling of Drugs and Poisons		
6			
Control of Scheduled Carcin	nogenic Substances		
Ingredient name No listed substance		<u>Schedule</u>	
Australia inventory (AICS)	: All components are listed or exempted.		
EU Classification	: Xi; R36/38 R43 N; R51/53		

16. Other information

Person who prepared the : Validated by DeSilva on 27.03.2013. MSDS

Date of previous issue : No previous validation.

✓ Indicates information that has changed from previously issued version.

Disclaimer

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.